

165 VR3

Polyglass kit

- Butyl surround
Promoting long life
- Shallow mounting midrange (39.5mm – 1^{1/2}")
Easy installation on the dashboard or on the A-pilar
- Polyglass cone
Neutral sound without coloration
- Zamak basket
Strong rigid chassis, non-magnetic, non-resonant
- 25mm (1") voice coil on Kapton® former
High power handling
- 85mm (3^{1/3}") magnet
High efficiency for more dynamic



- Aluminum/magnesium inverted dome TNB tweeter
Smooth and detailed treble, large and precise sound stage
- Neodymium magnet
High linearity tweeter
- Voice coil on aluminum former
Excellent heat dissipation characteristic

- Air core inductor with a low serial resistance
Insensitive to parasite, better sensitivity
- Adjustable tweeter level
Optimization of the tweeter level according to the location
- Polypropylene/aluminum capacitor
Natural reproduction of high frequencies
- 12/12/12dB/octave crossover
Optimum coupling of tweeter, midrange and woofer

165mm (6^{1/2}") woofer
25mm (1") voice coil
85mm (3^{1/3}") magnet
100mm (4") midrange
Neodymium magnet
45mm (1^{3/4}") TNB tweeter
Aluminum/magnesium inverted dome tweeter
12-12-12dB/octave 3-way crossover
(400Hz – 4kHz)
Adjustable tweeter level (0, -3, -6dB)
Max. power: 160W
Nom. power: 80W RMS
Sensitivity (2.83V/1m): 93dB
Frequency response: 55Hz – 28kHz
Accessories : grilles provided

It makes the difference:

- The 3-way state of the art kit audio contest contender
- Shallow mounting midrange for an optimized and easy installation
- Highest fidelity reproduction for an absolute realistic sound
- Large and precise sound stage
- Important dynamic
- The essentially of the Focal sound

