

# 130 VRS

## Polyglass kit

- Butyl surround  
**Promoting long life**
- Shallow mounting (49.5mm / 2")  
**Easy integration in the most exiguous spaces**
- Polyglass cone  
**Neutral sound without coloration**
- Zamak basket  
**Strong rigid chassis, non magnetic, non resonant**
- 32mm (1 1/4") voice coil on Kapton® former  
**High power handling**
- 38 SH neodymium magnet  
**High magnetic field for a high sensitivity**
- Voice coil cooling system  
**Optimized reliability, no dynamic compression**
- Air core inductor with a low serial resistance  
**Insensitive to parasites, better sensitivity**
- Adjustable tweeter level  
**Tweeter level setting according to the positioning**
- Polypropylene/Aluminum capacitor  
**Natural reproduction of high frequencies**



- Aluminum/magnesium inverted dome TNB tweeter  
**Smooth and detailed treble, large and precise sound stage**
- Dual push-pull neodymium magnet  
**Excellent linearity of the tweeter**
- Voice coil on aluminum former  
**High dissipation characteristics**

130mm (5") woofer  
 32mm (1 1/4") voice coil  
 38 SH neodymium magnet  
 45mm (1 3/4") TNB tweeter  
 Aluminum/magnesium inverted dome tweeter  
 12-18dB/octave 2-way crossover (4kHz)  
 Adjustable tweeter level (0, -3, -6dB)  
 Max. power: 100W  
 Nom. power: 50W rms  
 Sensitivity (2.8V/1m): 91dB  
 Frequency response: 80Hz – 28kHz  
 Accessories : grilles provided

### It makes the difference:

- Easy installation for all kind of vehicles (shallow mounting: 49,5mm / 2")
- Hi-Fi sound for an optimized realism
- Large and precise sound stage
- Important dynamic
- The essentially of the Focal sound

