

165 A3

3 way kit

- Painted DIN basket, 20% glass fiber filled ABS material
- Rigid basket, non-magnetic and non-resonant**
- All weather woven glass fiber cone
- Dynamic bass and accurate midrange, humidity resistant**
- Phase plug
- Regulates the midrange outside the axis**

- 25mm/2 layers voice coil on Kapton® support
- High power handling**
- 72mm and 85mm magnet
- High efficiency**
- Butyl surround
- Excellent cone damping**

- 3-level adjustable tweeter
- Level adaptation according to location**
- Low resistance self-induction coil
- Less loss, resistant to parasites**



- 20mm Ferrofluid voice coil
- Voice coil permanent cooling**
- Aluminum inverted dome
- Treble accuracy**

Technical characteristics :

165mm (6.5") Woofer
25mm (0.98") Voice coil
85mm (3.35") Magnet
100mm (3.94") Midrange
72mm (2.84") Magnet
TN44 inverted dome
3-way separate crossover 12/12dB/oct (300Hz-4kHz)
Adjustable tweeter level: +3, 0,-3dB
Max. power: 160W
Nom. power: 80W
Sensitivity (2.8V/1m: 90dB
Frequency response: 55Hz – 20kHz
(Grilles supplied)

It makes the difference:

- The new Access reference
- Excellent quality/price ratio
- 3-way kit sound quality

